




Image	Product Name	Specification	Price
	TORQUE BLACK/WHITE	Dimensions : 621 x 285 x 644 mm (DWH) Form Factor : Mid Tower Materials : Aluminum Mainboard Support : E-ATX, ATX, Micro-ATX, ITX Front Access & Controls : USB3.0 x 2, MIC/AUDIO(HD), Power, Type-C USB3.1 Side Panel : 4 mm Tempered glass (Both sides) + More	₱22,730.00
	DF800 Flux	Dimensions 479 x 220 x 488 mm (DWH) Form Factor Mid tower Materials Steel + Plastic Mainboard Support ATX , Micro-ATX, Mini-ITX Front Access & Controls Power, LED Control Button, 2 x USB3.0, MIC/HD-AUDIO Side Panel 4mm Tempered Glass Side Panel + More" Includes : 3 x 120mm ARGB fans in front 1 x 120mm fan (Reverse Fan) on PSU shroud 1 x 120mm fan in rear	₱5,420.00
	DF600 Flux	Dimensions 467 x 220 x 486 mm (DxWxH) Form Factor Mid tower Materials Steel + Plastic Mainboard Support ATX , Micro-ATX, Mini-ITX Front Access & Controls Power, LED Control Button, 2 x USB3.0, HD-AUDIO Side Panel 4 mm Tempered Glass Side Panel + More Includes : 3 x 120mm ARGB fans in front 1 x 120mm fan (Reverse Fan) on PSU shroud 1 x 120mm fan in rear	₱4,560.00
	NX410 Black	Dimensions 390 mm x 210 mm x 485 mm (DxWxH) 397 x 219 x 482 (DxWxH) (With handle) Form Factor Mid Tower Materials SPCC / ABS Mainboard Support ATX, micro-ATX, ITX Front Access & Controls Power, LED Control Button, USB3.0 x 1, USB2.0 x 2, HD-AUDIO Side Panel Tempered Glass Side Panel + More Includes : 2 x 140mm ARGB fans in front 1 x 120mm fan in rear	₱3,570.00
	NX410 White		₱3,700.00
	NX292	Dimensions 406 x 206 x 450mm (DWH) Form Factor Mid Tower Materials Steel + Plastic Mainboard Support E-ATX, ATX, Micro-ATX, ITX Front Access & Controls Power, Reset, USB 2.0 x2, USB 3.0 x 1, Headphone/Mic Combo Jack Side Panel Tempered glass + More Includes : 3 x 120mm Fixed mode RGB Fans in front 1 x 120mm fan in rear	₱2,645.00

 <p>NEW</p>	<p>NX290</p>	<p>Dimensions 404 x 206 x 450mm (DWH) Form Factor Mid Tower Materials Steel+Plastic Mainboard Support E-ATX, ATX, Micro-ATX, ITX Front Access & Controls Power, Reset, USB 2.0 x2, USB 3.0 x 1, Headphone/Mic Combo Jack Side Panel Tempered glass + More</p> <p>Includes : 3 x 120mm Fixed mode RGB Fans in front 1 x 120mm fan in rear</p>	<p>₱2,645.00</p>
 <p>NEW</p>	<p>NX201</p>	<p>Dimensions 438 x 193 x 463 mm (DWH) Form Factor Mid Tower Materials Steel + Plastic Mainboard Support ATX, Micro-ATX, ITX Front Access & Controls Power, LED Control Button, USB 3.0 x 1, USB 2.0 x 2, MIC/HD-AUDIO Side Panel Tempered glass + More</p> <p>Includes : 1 x 120mm fan in rear</p>	<p>₱2,380.00</p>
	<p>850Gold M White (NEW)</p>	<p>Type : ATX 12V 2.4 Modular : Fully Dimension : 150(L) x 140(W) x 86(H) Input Voltage : 100-240 VAC Input Current : 10A MAX Input Frequency Range : 50Hz-60Hz PFC : Active PFC Power Good Signal : 100-500ms Efficiency : Up To 92% Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO Output Capacity : 850W + More</p>	<p>₱5,100.00</p>
	<p>850Gold M Black</p>	<p>Type : ATX 12V 2.4 Modular : Fully Dimension : 150(L) x 140(W) x 86(H) Input Voltage : 100-240 VAC Input Current : 10A MAX Input Frequency Range : 50Hz-60Hz PFC : Active PFC Power Good Signal : 100-500ms Efficiency : Up To 92% Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO Output Capacity : 850W + More</p>	<p>₱6,740.00</p>
	<p>750Gold M Black</p>	<p>Type : ATX 12V 2.4 Modular : Fully Dimension : 150(L) x 140(W) x 86(H) Input Voltage : 100-240 VAC Input Current : 10A MAX Input Frequency Range : 50Hz-60Hz PFC : Active PFC Power Good Signal : 100-500ms Efficiency : Up To 92% Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO Output Capacity : 750W + More</p>	<p>₱5,750.00</p>

	<p>650Gold M Black</p>	<p>Type : ATX 12V 2.4 Modular : Fully Dimension : 150(L) x 140(W) x 86(H) Input Voltage : 100-240 VAC Input Current : 10A MAX Input Frequency Range : 50Hz-60Hz PFC : Active PFC Power Good Signal : 100-500ms Efficiency : Up To 92% Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO Output Capacity : 650W + More</p>	<p>₱5,100.00</p>
	<p>VP550P Plus</p>	<p>Product Name : VP550P PLUS Model Name : V3000A202H-18 Modular : Non-Modular Dimension (W x L x H) : 140(D)*150(W)*86(H) Input Voltage : 200-240 VAC ±10% Input Current : 5A Input Frequency Range : 50-60Hz PFC : Active PFC (>0.9 typical) Power Good Signal : 100-500ms Efficiency : 85% Typically Protection : OVP/SCP/OPP/NLO Output Capacity : 550W + More</p>	<p>₱3,970.00</p>
	<p>SIGNATURE 1000 PLATINUM</p>	<p>Product Name : SP1000 Platinum Model Name : X8000A505-18 Type : ATX Modular : Fully Dimension (W x L x H) : 150 x 170 x 86mm Warranty : 10 years Input Voltage : 100-240 Input Current : 13A – 6.5A Input Frequency Range : 47Hz – 63Hz PFC : APFC PFC at half / full load: >0.95 at AC 110v 60Hz(typical) >0.90 at AC 230v 50Hz(typical) Power Good Signal : 100 – 500mS Efficiency : At 20% / 50% / 100% load AC 115V internal, the power efficiency should be at least 90% / 92% / 89%. Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO Output Capacity : 1000W + More</p>	<p>₱13,790.00</p>
	<p>Atom B550 Bronze</p>	<p>Input voltage : 200-240v Input current : 6.3a Input frequency : 50hz Dimensions (l x w x h): 140 x 150 x 86 mm Fan size : 120mm Atx 24-pin connectors: 1 Eps 4+4-pin connectors: 1 Pci-e 6+2 pin connectors: 2 Sata connectors : 5 Peripheral 4-pin connectors: 3 Modular : non modular + More</p>	<p>₱2,650.00</p>
	<p>VP550P Plus</p>	<p>Modular : Non-Modular Dimension (W x L x H) : 140(D)*150(W)*86(H) Warranty : 3 years Input Voltage : 200-240 VAC ±10% Input Current : 5A Input Frequency Range : 50-60Hz PFC : Active PFC (>0.9 typical) Power Good Signal : 100-500ms Efficiency : 85% Typically Protection : OVP/SCP/OPP/NLO Output Capacity : 550W + More</p>	<p>₱2,710.00</p>



SYMPHONY 360 ARGB White

Fan
 Dimensions : 120 x 120 x 25mm
 Type PWM : ARGB LED Fan
 Speed : 800-1600rpm ± 100
 Airflow : 72 CFM max.
 Noise : 20-35db (A)
 Air pressure : 2.1mm H2o max
 Lifespan : 40000 hours at 25°C room, ambient 15-65% RH
 Connector : Fan : 4pin, ARGB: 3pin

Radiator
 Dimensions : 397 x 120 x 27 mm
 Material : Aluminum, Polycarbonate

Head
 Dimensions : 66.7 x 67 x 56 mm
 Connector : 3pin power
 WaterPressure : 1.2m
 Flow rate : 1.3L / min
 Lifespan : 70000 hours at 25°C room, ambient 15-65% RH
 Noise : ≤ 30dB(A)

Tube
 Dimensions : 8 x 10 x 380 mm

Socket Compatibility
 Intel Socket : LGA 1200 / 115X / 1366 / 1700 / 2011-V3 / 2066
 AMD Socket : FM2 / FM1 / AM3+ / AM2+ / AM2 / AM4

₱6,345.00



SYMPHONY 360 ARGB Black

Fan
 Dimensions : 120 x 120 x 25mm
 Type PWM : ARGB LED Fan
 Speed : 800-1600rpm ± 100
 Airflow : 72 CFM max.
 Noise : 20-35db (A)
 Air pressure : 2.1mm H2o max
 Lifespan : 40000 hours at 25°C room, ambient 15-65% RH
 Connector : Fan : 4pin, ARGB: 3pin



Radiator
 Dimensions : 397 x 120 x 27 mm
 Material : Aluminum, Polycarbonate




Head
 Dimensions : 66.7 x 67 x 56 mm
 Connector : 3pin power
 WaterPressure : 1.2m
 Flow rate : 1.3L / min
 Lifespan : 70000 hours at 25°C room, ambient 15-65% RH
 Noise : ≤ 30dB(A)





Tube
 Dimensions : 8 x 10 x 380 mm

Socket Compatibility
 Intel Socket : LGA 1200 / 115X / 1366 / 1700 / 2011-V3 / 2066
 AMD Socket : FM2 / FM1 / AM3+ / AM2+ / AM2 / AM4

₱6,015.00

	<p>SYMPHONY 240</p>	<p>Fan Dimensions : 120 x 120 x 25 mm Type : PWM ARGB LED Fan Speed : 800-1600rpm ± 100 Airflow : 72 CFM max. Noise : 20-35db (A) Air pressure : 2.1mm H2o max Lifespan : 40000 hours at 25°C room, ambient 15-65% RH Connector : Fan: 4pin, ARGB: 3pin</p> <p>Radiator Dimensions : 277 x 120 x 27 mm Material : Aluminum, Polycarbonate</p> <p>Head Dimensions : 66.7 x 67 x 56 mm Connector : 3pin power Water Pressure : 1.2m Flow rate : 1.3L / min Lifespan : 70000 hours at 25°C room, ambient 15-65% RH Noise : ≤ 30dB(A)</p> <p>Tube - Dimensions : 8 x 10 x 380 mm</p> <p>Socket Compatibility Intel Socket: LGA 1200 / 115X / 1366 / 1700 / 2011-V3 / 2066 AMD Socket: FM2 / FM1 / AM3+ / AM2+ / AM2 / AM4</p>	<p>₱4,890.00</p>
	<p>Kuhler k240 RGB</p>	<p>Fan Dimensions : 120 x 120 x 25mm Type : PWM RGB LED Fan Speed : 900-2000rpm±10% Airflow : 77 CFM Noise : 20-36db (A) Lifespan : 40000 hours at 25°C room, ambient 15-65% RH Connector : 4 pin</p> <p>Radiator Dimensions : 288 x 120 x 27mm Material : Aluminum</p> <p>Pump Dimensions : 60 x 60 x 31 mm Connector : SATA power Water Pressure : 1m±0.2m Flow rate : 1.5L/min Lifespan : 50000 hours at 25°C room, ambient 15-65% RH Noise : ≤ 36dB (A)</p> <p>Tube - Dimensions : 8 x 10 x 348 mm</p> <p>Socket Compatibility Intel Socket : LGA 2066 / 2011-V3 / LGA2011 / LGA1366 / LGA1156 / 1155 / 1151 / 1150 AMD Socket: AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1</p>	<p>₱4,760.00</p>

	<p>C400 Glacial</p>	<p>Model Name : C400 Glacial Cooling Type : Air cooling Product Dimension : 125 x 76 x 155 mm</p> <p>Fan</p> <p>Type : PWM Fan Speed : 600 - 1800 RPM + 10% Airflow : 77 CFM Noise Level : 20.3 db(A) - 34.5 db(A) Lifespan : 50000 hrs Connector : 4-Pin LED Effect : Pure White LED</p> <p>Compatibility Intel : LGA 775 / 1150 / 1151 / 1155 / 1156 / 1200 / 1366 / 2011 / 2066 AMD : FM2 / FM1 / AM3+ / AM3 / AM2 + / AM2 / AM4 Net Weight : 755 g Gross Weight : 935 g Package Size : 234 x 174 x 111 mm</p> <p>Includes : Intel LGA 1700 CPU Cooler Bracket</p>	<p>₱2,050.00</p>
	<p>C400</p>	<p>CPU Support: Intel: 775/1150/1151/1155/1156/1200/1366/2011/2066 AMD: FM2/FM1/AM3/AM3+/AM2+/AM2/AM4 Fan: 120 mm Blue LED Fan with PWM (800 - 1.900 RPM) Airflow: Max. 77 CFM - Noise: 20.3 - 34.5 dBA</p> <p>Includes : Intel LGA 1700 CPU Cooler Bracket</p>	<p>₱1,850.00</p>
	<p>A400 RGB</p>	<p>Product Dimension : 125 x 76 x 155 mm (D x W x H)</p> <p>Fan :</p> <p>Type : PWM Fan Speed : 600 - 1800 RPM + 10% Airflow : 77 CFM Noise Level : 20.3 db(A) - 34.5 db(A) Lifespan : 50000 hrs Connector : 4-Pin LED Effect : RGB LED</p> <p>Compatibility Intel : LGA 775 / 1150 / 1151 / 1155 / 1156 / 1200 / 1366 / 2011 / 2066 AMD : FM2 / FM1 / AM3+ / AM3 / AM2 + / AM2 / AM4</p> <p>Net Weight : 748 g Gross Weight : 861 g Package Size : 166 x 105 x 215 mm (D x W x H)</p>	<p>₱1,720.00</p>
	<p>A40Pro</p>	<p>CPU Support: Intel: 775/1150/1151/1155/1156/1200/1366 AMD: FM1/FM2/AM3/AM3+/AM2+/AM2/AM4 Fan: 92 mm Blue LED Fan with PWM (800 - 1.900 RPM) Airflow: Max. 41 CFM - Noise: 20.3 - 34.5 dBA</p> <p>Includes : Intel LGA 1700 CPU Cooler Bracket</p>	<p>₱1,190.00</p>

	<p>Prizm 120 ARGB 3+2+C</p>	<p>Fan Type : PWM Fan Dimensions (mm) : 120*120*25 mm Bearing Type : Hydraulic LED Type : Addressable RGB Fan Speed (RPM) : 2000 max. Airflow (CFM) : 45.03 max. Air Pressure (mmH2O) : 2.56 max. Fan Noise Level (dBA) : 32.6 max. Lifespan : 40000 hours Connector : Fan: 4 pin ; ARGB: 3 pin Rated Voltage : FAN: DC12V ; LED: DC5V Operating Voltage : FAN: DC6.0-13.8V; LED: DC4.5-5.3V Rated Current (A) : FAN: 0.18A±20% ; LED: 0.80A±20% Fan Control Box : ARGB port x 5, PWM fan port x 5, SATA, Mode, External LED CTRL, M/B Sync, LED Speed LED strips Length : 40cm</p>	<p>₱2,980.00</p>
	<p>Prizm 120 ARGB 5+C</p>	<p>Fan Type : PWM Fan Dimensions (mm) 120*120*25 mm Bearing Type Hydraulic LED Type Addressable RGB Fan Speed (RPM) 2000 max. Airflow (CFM) 45.03 max. Air Pressure (mmH2O) 2.56 max. Fan Noise Level (dBA) 32.6 max. Lifespan 40000 hours Connector Fan: 4 pin ; ARGB: 3 pin Rated Voltage FAN: DC12V ; LED: DC5V Operating Voltage FAN: DC6.0-13.8V; LED: DC4.5-5.3V Rated Current (A) FAN: 0.18A±20% ; LED: 0.80A±20%</p>	<p>₱3,240.00</p>
	<p>Prizm X 120 ARGB 3+C</p>	<p>Fan Type : PWM Fan Dimensions : 120*120*25MM Bearing Type : Hydraulic LED Type : ARGB Fan Speed : 500-2000±10% RPM Airflow : 10-45.21CFM Air Pressure : 0.30-2.56mmH2O Fan Noise Level : 20.0-32.6dBA Lifespan : 40000 Connector : Fan: 4-pin / LED: 3-pin Rated Voltage : Fan: DC 12V / LED: DC 5V Operation Voltage : Fan: DC 6.0-13.8V / LED: DC 4.5-5.3V Rated Current : Fan: 150mA±20% / LED: 900mA(Max)</p>	<p>₱2,580.00</p>
	<p>Prizm 120 ARGB</p>	<p>Fan Type : PWM Fan Dimensions (mm) 120*120*25 mm Bearing Type Hydraulic LED Type Addressable RGB Fan Speed (RPM) 2000 max. Airflow (CFM) 45.03 max. Air Pressure (mmH2O) 2.56 max. Fan Noise Level (dBA) 32.6 max. Lifespan 40000 hours Connector Fan: 4 pin ; ARGB: 3 pin Rated Voltage FAN: DC12V ; LED: DC5V Operating Voltage FAN: DC6.0-13.8V; LED: DC4.5-5.3V Rated Current (A) FAN: 0.18A±20% ; LED: 0.80A±20%</p>	<p>₱470.00</p>